

Cord Caddies

Safe, Dependable Power-to-Go in a Rugged, Flexible Design

The easy way to get electrical power from source to site.

Safety, durability and flexibility to bring power where you need it are all part of the package with K&H Cord Caddies.

The fully grounded frame and optional GFCI outlets provide safe operation, with heavy-duty, powder-coated steel construction for durability.



A variety of cord options and outlet configurations are available.

K&H Cord Caddies can also be wired for data lines.

APPLICATIONS

- Construction
- Groundskeeping
- Manufacturing
- Maintenance
- Utilities

FEATURES

- Safety-yellow, powder-coated steel end plates
- Fully grounded assembly
- Durable solid steel frames
- Ground Fault Circuit protection
- No collector rings, brushes or slip rings
- Dual duplex receptacles

OPTIONS

- 15 or 20 amps
- GFCI protection
- Dirt- and dust-resistant outlet covers
- Yellow or black SOOW power cords
- A variety of cord lengths and types



K&H Industries, Inc.

The Permanent Name in
Temporary Lighting & Power

Call: 716-549-0135

Click: www.KHindustries.com




Cord Caddies

Specifications



K&H Cord Caddies can be used horizontally or vertically for flexibility in almost any work environment.

- **Weight:** 15 lbs. without cord; weight varies with cord length installed
- **Cord:** 14- or 12-AWG, 3 conductors SOOW 600 VAC
- **Cord Lengths:** 0' – 200'
- **Electrical Operation:**
 - **Voltage:** 120 VAC
 - **Current:** 15- or 20-amp
 - **Receptacles/Plug:** NEMA 5-15 or NEMA 5-20
- **Receptacles:** Two commercial-grade duplex
- **Attachment Plugs:** Industrial grade, rubber jacketed
- **Special Applications:** K&H can customize your reel with a variety of other cord and cover options.




Catalog Numbers

Note: Amperage ratings based on cord completely unreeled from caddy.

Custom configurations available upon request.


K&H Cord Caddies

CORD CADDIES WITH 15-AMP, 14/3 POWER CORD, NEMA 5-15 RECEPTACLES

Blade Configuration	Cord Length	Black SOOW Cord		Yellow SOOW Cord	
		without GFCI	with GFCI	without GFCI	with GFCI
 15 Amp NEMA 5-15	0'	CCN-515A	CCG-515A	CCN-515A	CCG-515A
	50'	CCN-515-B14K	CCG-515-B14K	CCN-515-Y14K	CCG-515-Y14K
	75'	CCN-515-B14P	CCG-515-B14P	CCN-515-Y14P	CCG-515-Y14P
	100'	CCN-515-B14U	CCG-515-B14U	CCN-515-Y14U	CCG-515-Y14U
	125'	CCN-515-B14V	CCG-515-B14V	CCN-515-Y14V	CCG-515-Y14V
	200' *	CCN-515-B14Y	CCG-515-B14Y	CCN-515-Y14Y	CCG-515-Y14Y

*Actual rating of 12 amps based on 200' of 14/3 cord completely unreeled from caddy.

CORD CADDIES WITH 20-AMP, 12/3 POWER CORD, NEMA 5-20 RECEPTACLES

Blade Configuration	Cord Length	Black SOOW Cord		Yellow SOOW Cord	
		without GFCI	with GFCI	without GFCI	with GFCI
 20 Amp NEMA 5-20	0'	CCN-520A	CCG-520A	CCN-520A	CCG-520A
	50'	CCN-520-B12K	CCG-520-B12K	CCN-520-Y12K	CCG-520-Y12K
	75'	CCN-520-B12P	CCG-520-B12P	CCN-520-Y12P	CCG-520-Y12P
	100'	CCN-520-B12U	CCG-520-B12U	CCN-520-Y12U	CCG-520-Y12U
	125'	CCN-520-B12V	CCG-520-B12V	CCN-520-Y12V	CCG-520-Y12V

Ordering Information

K&H Cord Caddies are available from K&H Industries. For more information:

- Call: 716-549-0135
- Click: www.KHindustries.com
- Visit: 8656 Delameter Road, Angola, NY 14006

